

ENHANCEMENT TO TRANSACTION ORDER QUEUE

BY:

PARAS A. SHAH
10738 NORTH BELMONT COURT
HOUSTON, TX 77065

“EXPRESS MAIL” MAILING LABEL
Number US 652 335 258 US
Date of Deposit: February 8, 2001

Pursuant to 37 C.F.R. § 1.10, I hereby certify that I am personally depositing this paper or fee with the U.S. Postal Service, “Express Mail Post Office to Addressee” service on the date indicated above in a sealed envelope (a) having the above-numbered Express Mail label and sufficient postage affixed, and (b) addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Signature: Lynda Howell
Printed Name: Lynda Howell

ENHANCEMENT OF TRANSACTION ORDER QUEUE

FIELD OF THE INVENTION

The present invention relates generally to an enhancement of a transaction order queue.

5 Particularly, the present invention facilitates the queueing of many transaction entries within a single device and ensures that PCI/PCI-X ordering rules are not violated.

BACKGROUND OF THE RELATED ART

10 This section is intended to introduce the reader to various aspects of art, which may be related to various aspects of the present invention, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

15 A conventional computer system typically includes one or more central processing units (CPUs) and one or more memory subsystems. Computer systems also typically include peripheral devices for inputting and outputting data. Some common peripheral devices include, for example, monitors, keyboards, printers, modems, hard disk drives, floppy disk drives, and network
20 controllers. The various components of a computer system communicate and transfer data using various buses and other communication channels that interconnect the respective communicating components.

One of the important factors in the performance of a computer system is the speed at which the CPU operates. Generally, the faster the CPU operates, the faster the computer system can complete a designated task. Another method of increasing the speed of a computer is using multiple CPUs, commonly known as multiprocessing. With multiple CPUs, tasks may be executed substantially in parallel as opposed to sequentially.

However, the addition of a faster CPU or additional CPUs can result in different increases in performance among different computer systems. Although it is the CPU that executes the algorithms required for performing a designated task, in many cases, it is the peripherals that are responsible for providing data to the CPU and storing or outputting the processed data from the CPU. When a CPU attempts to read or write to a peripheral, the CPU often “sets aside” the algorithm which it is currently executing and diverts to executing the read/write transaction, (also referred to as an input/output transaction or an I/O transaction) for the peripheral. As can be appreciated by those skilled in the art, the length of time that the CPU is diverted is typically dependent on the efficiency of the I/O transaction.

Although a faster CPU may accelerate the execution of an algorithm, a slow or inefficient I/O transaction process associated therewith can create a bottleneck in the overall performance of the computer system. As the CPU becomes faster, the amount of time it expends executing algorithms becomes less of a limiting factor compared to the time expended in performing an I/O transaction. Accordingly, the improvement in the performance of the computer system that could theoretically result from the use of a faster CPU or the addition of another CPU may become substantially curtailed by the bottleneck created by the I/O transactions. Moreover, it can be readily

appreciated that any performance degradation due to such I/O bottlenecks in a single computer system may have a stifling affect on the overall performance of a computer network in which the computer system is disposed.

5 As the CPUs have increased in speed, the logic controlling the transactions has evolved to accommodate the I/O transactions. Such logic, usually referred to as a “bridge,” is typically an application specific integrated circuit (ASIC). For example, Peripheral Component Interconnect (PCI) logic was instilled within buses and bridges to govern transactions between a peripheral device and the CPU.

10 Today, PCI logic has evolved into the Peripheral Component Interconnect Extended (PCI-X) to form the architectural backbone of the computer system. PCI-X logic has features that improve upon the efficiency of communication between peripheral devices and the CPU. For instance, PCI-X technology increases bus capacity to more than eight times the conventional PCI bus bandwidth. For example, a 133 MB/s system with a 32 bit PCI bus running at 33 MHz is increased to a 1066 MB/s system with the 64 bit PCI bus running at 133 MHz. An additional feature of the new PCI-X logic is that it can provide backward compatibility. Backward compatibility refers to a feature where PCI enabled logic devices may be operable with systems incorporating PCI-X logic. However, the bus enabling the PCI device will operate at the slower
15 PCI speed even though PCI-X devices may be located on the same bus.
20

As PCI-X logic is incorporated into the next generation of buses and bridges, it becomes important to handle transactions efficiently. Generally, peripheral devices initiating transactions

will target the PCI-X bridge or a host bridge. As a transaction is initiated, a buffer is allocated within the bridge. The bridge stores the information about the transaction, such as its starting address, length and so on. Thus, the PCI-X bridge stores the transaction and replies to the requesting agent according to priority.

5

Transaction order queues (TOQ) may be utilized to prioritize transactions flowing through a bridge. Generally, TOQs process large quantities of transactions, typically greater than twenty; however only one entry can be enqueued in a particular clock cycle. This limitation is problematic in applications in which multiple transactions may be received in a single clock cycle. There are applications when a requestor may request multiple unrelated transactions in a single clock cycle. In these situations, the enhancement described below maintains transaction ordering while allowing multiple transaction entries to be stored.

The present invention may be directed to one or more of the problems set forth above.

SUMMARY OF THE INVENTION

Certain aspects commensurate in scope with the originally claimed invention are set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of certain forms the invention might take and that these aspects are not intended to limit the scope of the invention. Indeed, the invention may encompass a variety of aspects that may not be set forth below.

In accordance with one aspect of the present invention, there is provided a method whereby a transaction order queue is used to prioritize transactions flowing through a bridge. The method manages a combinational decode and ordering logic device, which selects a single transaction entry to send to the main transaction order queue. Due to the ordering rules, posted write transactions are selected first, if present. After posted writes, either delayed/split transactions or read completions transaction entries may be sent to the TOQ. In this particular embodiment, the combinational decode and ordering logic device operates to prioritize read completion transactions before delayed/split transactions. Entries for read completions transactions are selected and then delayed/split transactions after processing posted write transactions. Furthermore, the present technique enqueues one transaction entry into the TOQ per clock cycle.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

FIG. 1 illustrates a diagram of an exemplary computer system in accordance with the present invention;

FIG. 2 illustrates a logic diagram of an enhancement to a transaction order queue;

FIG. 3 illustrates elements representative of the combinational encode device with respect to the enhancement of the transaction order queue; and

FIG. 4 illustrates a flowchart representing the steps for processing transaction entries in a transaction order queue utilizing an exemplary technique.

DESCRIPTION OF SPECIFIC EMBODIMENTS

5 One or more specific embodiments of the present invention will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

10 Turning now to the drawings, and referring initially to Figure 1, a multiprocessor computer system, for example a Proliant 8500 PCI-X from Compaq Computer Corporation, is illustrated and designated by the reference numeral 10. In this embodiment of the system 10, multiple processors 12 control many of the functions of the system 10. The processors 12 may be, for example, 15 Pentium, Pentium Pro, Pentium II Xeon (Slot-2), or Pentium III processors available from Intel Corporation. However, it should be understood that the number and type of processors are not critical to the technique described herein and are merely being provided by way of example. 20

Typically, processors 12 are coupled to a processor bus 14. As instructions are sent and received by the processors 12, the processor bus 14 transmits the instructions and data between the individual processors 12 and a switch 16. The switch 16 directs signals between the processor bus 14, cache accelerator 18, and a memory controller 20. A crossbar switch 16 is shown in this embodiment, however, it should be noted that any suitable type of switch may be used. When the data is retrieved from the memory 22, the instructions are sent via the memory controller 20. The memory controller 20 may be of any type suitable for such a system, such as a Profusion memory controller. It should be understood that the number and type of memory, switches, memory controllers, and cache accelerators are not critical to the technique described herein, and are merely being provided by way of example.

The memory 22 in the system 10 is generally divided into groups of bytes called cachelines. Bytes in a cacheline may comprise several variable values. Cachelines in the memory 22 are moved to a cache for use by the processors 12 when the processors 12 request data stored in that particular cacheline.

The switch 16 is also coupled to an I/O bus 24. As mentioned above, the switch 16 directs data to and from the processors 12 through the processor bus 14, and either the cache accelerator 18 or the memory 22 through the use of the memory controller 20. In addition, data may be sent through the I/O bus 24 to multiple PCI-X bridges 26 A-D. The I/O bus 24, in this embodiment, is shown coupled to PCI-X bridges 26 A-D. Further, each PCI-X bridge 26 A-D is coupled to multiple PCI-X buses 28 A-D. Finally, each PCI-X bus 28 A-D terminates at a series of slots or I/O interfaces 30 A-D.

The PCI-X bridges 26 A-D contain logic that processes input/output transactions.

Generally, ASICs are the implementation of the PCI-X bridges 26 A-D. The PCI-X bridges 26 A-D may include address and data buffers, as well as arbitration and bus master control logic for the PCI-X buses 28 A-D. The PCI-X bridges 26 A-D may also include miscellaneous logic, such as counters and timers as conventionally present in personal computer systems, an interrupt controller for both the PCI and I/O buses, and power management logic.

Generally, a transaction is initiated by a requestor, e.g., a peripheral device, via the I/O interface 30 A-D. The transaction is then sent to one of the PCI-X buses 28 A-D depending on the peripheral device utilized and the location of the I/O interface 30 A-D. The transaction is then directed towards the PCI-X bridge 26 A-D. Logic devices within the bridge 26 A-D generally allocate a buffer where data returned from the memory 22 may be stored. Once the buffer is allocated, the transaction request is directed towards the processor 12 and then to the memory 22. Once the requested data is returned from the memory 22, the data is stored within the respective bridge 26 A-D. The logic device within the bridge 26 A-D operates to read and deliver the data to the requesting peripheral device. As mentioned above, if the transaction is conducted through a peripheral device that is not PCI-X enabled, the PCI-X buses 28 A-D and the PCI-X bridges 26 A-D administer the transaction request using PCI specifications. Tape drives, CD-ROM devices, or other peripheral devices may be connected to the slots or I/O interfaces 30 A-D.

As mentioned above, the bridge 26 A-D may be an ASIC chip that contains logic that operates many of the functions described here. For instance, logic programmed within the ASIC chip controls the buffer read function. Furthermore, the ASIC chip may also contain logic

specifying ordering rules, buffer allocation, specifying transaction type, and logic for receiving and delivering data.

The bridge 26 A-D may receive multiple simultaneous transactions which requires the
5 modifying of a transaction order queue. Typically, only one entry can be enqueued in a particular clock cycle. It should be noted that although a single transaction is initiated, the transaction is divided into separate entries to facilitate the data retrieval and delivery process. For example, a read completion transaction may be divided into multiple entries which are transmitted to the TOQ creating the a scenario where multiple entries may be received by the TOQ in a single clock cycle.
10 Further, multiple entries may also be received in a single clock cycle when transactions running at a frequency normal to the processor bus enters the slower running bridge 26 A-D simultaneously.

Figure 2 illustrates a system diagram depicting the logic governing an example of the enhanced transaction order queue (TOQ) 31 that is included within the bridge 26 A-D. In this
15 particular embodiment, transaction entries 32 may be directed to the enhanced transaction order queue 31, where the entries 32 are first received by a combinational encode logic device 34. The combinational encode device 34 directs the transaction entries 32 toward a plurality of registers 36. A more detailed description of the combinational encode device 34 will be discussed below. The registers 36 may be of any type suitable for storing multiple transaction entries 32. It should be
20 noted that these registers 36 do not maintain ordering information, but rather store the transaction entry 32 being initiated, for example, a read completion, posted write, or delayed/split transaction.

The combinational decode and ordering device 38 receives the entries 32 from the registers 36 and prioritizes the entries 32 according to PCI-X specifications. As described in greater detail below, the combinational decode and ordering device 38 delivers the entries 32 according to priority via a logic device 40 for enqueueing to the “original” transaction order queue 42. Generally, a transaction order queue is implemented within the bridge, thus the present invention is an enhancement to that transaction order queue. Therefore, the transaction order queue 42 is referred to as the “original” transaction order queue.

A single entry 32 from the registers 36 is delivered to the logic device 40 every clock cycle. Once the transaction order queue 42 processes the transaction entry 32, it delivers the prioritized entry 32 to the dequeue logic device 44. The dequeue logic device 44 delivers the requested information to the buffer 36 as output 46. Thus, the ordering rules are maintained and the PCI-X transaction is completed within the transaction order queue.

It should be noted that the combinational encode device 34 and the combinational decode and ordering device 38 may be fabricated as part of the application specific integrated circuit that functions in concert with the enhanced transaction order queue 31. It should also be noted that the transaction entry 32 is transmitted from the buffer 36 containing information regarding the type of transaction and the location at which the transaction is located within the buffer 36. Generally, a transaction entry contains five bits of data which identifies the transaction. Specifically, two bits refer to the type of transaction and the three additional bits identify the location of the transaction data within the buffer 36.

Fig. 3 illustrates the elements operating to process the transaction entries 32 within logic device 34. The combinational encode logic device 34 primarily functions to manage the registers that store the transaction entries 32 efficiently. Combinational encode logic device 34 includes a series of multiplexers 35 A-D, which are adapted to receive multiple simultaneous transaction entries 32. In the present embodiment, multiplexers 35 A-D are configured to preserve transaction entries 32 that are saved within the register 36. However, if the register 36 is available, then a new entry 32 is transmitted to the register 36 via the multiplexer 35 A-D. For example, if the register 36 is holding an entry 32 for a particular clock cycle, then the multiplexer 35 A-D will output the same value for the particular entry 32 until the register 36 is cleared and that particular entry 32 is sent to the combinational decode and ordering logic device 38. Thus, the multiplexer 35 A-D is adapted to facilitate the input of a new transaction entry 32 or permitting the register 36 to retain the current entry 32 until it is transmitted into the combinational decode and ordering logic device 38. It should be understood that the combinational encode logic 34 does not prioritize the transaction entries; rather it functions to prevent the registers 36 from overflowing. Thus, the transactions are not prioritized but rather collected and distributed in an efficient manner. Although, the present invention illustrates one method of encoding entries, alternative logic may be utilized to produce similar results. For example, additional logic gates such as AND gates are generally implemented along with multiplexers to encode the transaction entries 32.

Figure 4 illustrates a flowchart of the steps taken within the combinational decode and ordering logic device referenced by numeral 38 in Fig. 2. The primary purpose for the combinational decode and ordering logic device 38 is to select a single transaction entry 32 from the registers 36 to send to the transaction order queue as referenced by 42 in Fig. 2. Due to PCI-X

ordering rules, posted write transactions are selected first to be enqueued. Thus, once the registers 36 store the transaction entry, it is prioritized accordingly by the combinational decode and ordering device 38, which orders the entries 32 according to PCI-X specifications. Once the entries 32 are prioritized, the combinational decode and ordering device 38 forwards the transaction entry 32 to the logic device 40 for enqueueing into the TOQ 42. The logic device 38 determines if a posted write entry is present (block 50). Thus, if the entry 32 is determined to be a posted write transaction, then the entry 32 is sent to the original transaction order queue (block 52). However, if the transaction entry 32 is determined not to be a posted write transaction, then the combinational decode and ordering device 38 determines whether the transaction entry is a read completion (block 54). If the combinational decode and ordering device 38 determines that the transaction entry is a read completion, then the transaction entry is transmitted to the transaction order queue 42 (block 56). Once the specific transaction entry 32 is enqueued according to priority, the registers 36 are cleared of the corresponding entry. It should be noted that for read completion transactions, the entry 32 may include additional bits that are required to store and retrieve data from the cachelines. If the transaction is determined not to be a read completion, then the combinational decode and ordering device 38 determines whether the transaction entry is a delayed/split transaction request (block 58). If the transaction is a delayed/split transaction request, then the transaction entry is transmitted into the transaction order queue 42 (block 60). However, if the transaction is not a delayed/split transaction request then no entry is sent to the TOQ (block 62).

Although, a specific ordering pattern is illustrated by the flowchart in Fig. 3, it should be known that various different ordering mechanisms may be adapted for any purpose necessary in the system 10. For example, the one clock cycle may also be adjusted according to PCI-X

specifications necessary to achieve an efficient transaction order queue. Also, the logic devices in the enhanced feature may be configured to incorporate additional features to create a more efficient transaction order queue. Further, additional logic devices including logic to dequeue multiple transaction entries within one clock cycle, may be adapted.

5

While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Rather, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2